



> PRINT > COPY > SCAN > FAX

ECOSYS M6035cidn
ECOSYS M6535cidn

A4 COLOUR MULTIFUNCTIONALS

INTUITIVE COLOUR ALL-ROUNDERS



- > Up to 35 A4 pages per minute in colour and black and white
- > Time to first copy 9/11 seconds in colour and black and white
- > Double-sided print, copy, scan and fax* functionality as standard
- > High speed controller with 1 GHz CPU and 1 GB memory
- > High speed scan with up to 60ipm via a 75 sheet document processor
- > 7-inch full colour touch panel screen provides ease of use
- > HyPAS solution platform enables powerful customisation
- > Mobile printing support including AirPrint, Mopria and KYOCERA Mobile

*Only ECOSYS M6535cidn

KYOCERA has developed these new A4 colour devices, designed specifically for small and medium-sized work groups, offering both reliability and fast output speeds. Both devices are equipped with a convenient touch panel which increases their usability by providing direct access to the numerous functions available as standard. Document workflow can be further optimised using dedicated program keys and KYOCERA's integrated HyPAS platform. KYOCERA's exceptional long-life components ensure low running cost and reduced impact on the environment.



ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means toner is the only consumable for the first 200,000 pages. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility

ECOSYS M6035cidn | ECOSYS M6535cidn
GENERAL

Technology: KYOCERA ECOSYS, Colour Laser, HYPAS™ solution platform
Control panel display: 17.8 cm (7 inch) full-colour touch panel display, tilt in 3 steps (0, 10, 20 degree)
Engine speed: Up to 35 pages A4 per minute in colour and black and white
Resolution: 600 x 600 dpi, multibit technology for print quality of up to 9,600 x 600 dpi (print), 600 x 600 dpi, 256 greyscales per colour (scan / copy)
Duty cycle: Maximum: 100,000 pages per month
 Maximum average: 3,333 pages per month
 Average: 2,500 pages per month
Warm-up time: Approx. 25 seconds or less
Time to first print: Approx. 7 / 8.5 seconds or less in black and white / colour
Time to first copy: Approx. 9 / 11 seconds or less in black and white / colour
CPU: PowerPC 4655 / 1 GHz
Memory: Standard 1,024 MB, max. 2,048 MB
Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT) Slot for optional internal print server or SSD hard disc Slot for optional SD/SDHC-Card
Integrated accounting: 100 department codes
Dimensions (W x D x H): Main unit: 475 x 558 x 616 mm
Weight: Main unit: Approx. 35.3 / 35.4 kg
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption:
 Copy / Print: 551 W / 537 W
 Ready mode: 73 W
 Sleep-mode: 2.1 W
Noise (Sound pressure level: ISO 7779 / ISO 9296):
 ECOSYS M6035cidn ECOSYS M6535cidn
 Copy / Print colour: 49.9 dB(A) LpA 49.7 dB(A) LpA
 Quiet mode in colour: 46.4 dB(A) LpA 46.5 dB(A) LpA
 Sleep mode : Immeasurably low
Safety standards: GS, TÜV, CE
 This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
PAPER HANDLING
 All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity: 100-sheet multi-purpose tray; 60 – 220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – 216 x 356 mm) 250-sheet universal cassette; 60 – 163 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (105 x 148 – 216 x 356 mm). Max. input capacity with options: 1,850 sheets
Duplex functionality as standard: Double-sided printing; 60 – 163 g/m²; A4, A5, B5, Letter, Legal
Reversing document processor: 75-sheet, 50–120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 to 216 x 356 mm)
Output capacity: Max. 250 sheets face-down with paper full sensor

PRINT FUNCTIONS

Control language: PRESCRIBE IIc
Emulations: PCL 6 (PCL 5c/PCL-XL), PostScript 3 (KPDLL 3), PDF Direct Print 1.7, XPS Direct Print
Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 93 scalable fonts for PCL/PostScript, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13, EAN128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)
COPI FUNCTIONS
Max. original size: A4 / Legal
Continuous copying: 1-999
Zoom range: 25–400 % in 1 % steps
Preset magnification ratios: 7 Reductions / 5 Enlargements
Exposure mode: Auto, manual: 9 steps
Image adjustments: Text + Photo, Photo, Text, Map, Printed document
Features: Auto Colour Mode, Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail (SMTP over SSL), Scan-to-FTP (FTP over SSL), Scan-to-SMB, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network)
Scan speed: 60 ipm (300 dpi, A4, black and white), 40 ipm (600 dpi, A4 black and white, 300 dpi, A4, colour)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales-per colour)
Max. scan size: A4, Legal
Original recognition: Text + Photo, Photo, Text, Light Text/ Fine Line, Text (for OCR)
File types: TIFF, PDF, PDF/A , high compression PDF, encrypted PDF, JPEG, XPS
Compression method: MMR / JPEG
Features: Integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB / FTP folder, print) at once

FAX FUNCTIONS (ECOSYS M6535cidn only)

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: Less than 3 seconds
Scanning speed: 2.5 seconds
One-touch dial: 100 numbers
Address book: 200 entries
Scanning density:
 Normal: 200 x 100 dpi, Fine: 200 x 200 dpi
 Superfine: 200 x 400 dpi, Ultrafine: 400 x 400 dpi
 Halftone: 256 greyscales

Maximum original size: A4, Legal
Compression method: JBIG, MMR, MR, MH
Memory reception: 256 sheets or more
Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

OPTIONS

PF -5100 Paper feeder (max 3 units):
 Max. 500 sheets; 60–220 g/m²; A4, A5, B5, Letter, Legal, Custom (148x 210 mm to 216 x 356 mm)
MS-5100 Convenient Stapler:
 20 sheets, one position semi-automatic stapling, includes 1,500 staples
CB-5100H Cabinet: Wooden desk with storage capacity. Approx. 39 cm x 53 cm x 50 cm (WxDxH)
CB-5100L Cabinet: Wooden desk with storage capacity. Approx. 39 cm x 53 cm x 37 cm (WxDxH)
Memory upgrade: MDDR3-1GB: 1.024 MB
HD-6 SSD: 32 GB for easy document management
HD-7 SSD: 128 GB for easy document management
Data security kit (E): in line with security level EAL3
USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available
IC Card Reader Holder 10: To integrate the USB IC Card Reader
UG-33: ThinPrint support

Optional interfaces:
IB-50 Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ-45)
IB-51 Wireless LAN: 802.11b/g/n

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798
Toner-Kit TK-5150C, TK-5150M, TK-5150Y: cyan, magenta, yellow toner yield 10,000 pages A4
 Starter toner: cyan, magenta, yellow toner yield 5,000 pages A4
Toner-Kit TK-5150K: black toner yield 12,000 pages A4
 Starter toner: black toner yield 6,000 pages A4
SH-13 Staple cartridge: 2 x 1,500 staples for MS-5100

WARRANTY

1-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or maximum 200,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.

KYO LIFE The up to 5-year on-site warranty extension for printer and options.



KYOCERA Document Solutions (UK) Ltd, Eldon Court, 75-77 London Road, Reading RG1 5BS
 Tel: 0118 931 1500, Fax: 0118 931 1108
 www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country

YOUR KYOCERA BUSINESS PARTNER

