

> PRINT > COPY > SCAN > FAX

TASKalfa 3253ci

A4/A3 (SRA3) COLOUR MULTIFUNCTIONAL

THE PERFECT FIT FOR YOUR TEAM



Intuitive 10.1"colour touch screen.



Outstanding image quality - standard 1200 x 1200dpi. Flexible paper handling from A6 to SRA3







Standard data security kit ensures the highest levels of document encryption.





mopria



Fiery™ controller ensures the highest productivity colour print output.

The all new TASKalfa 3253ci incorporates the very latest KYOCERA technology to ensure unrivalled print quality and productivity. A wide range of productivity enhancing options allows you to tailor this device to meet your existing workflow processes to be the perfect fit for your team. SRA3 print capability combined with the optional Fiery ™ controller allows you to print the highest quality printed documents for both your internal and external clients. The in-built 10.1" full colour touch screen also allows you to quickly and easily navigate through the myriad of digital functions incorporated in this device. A standard data security function also allows peace of mind, knowing that all documents that are sent to and printed from or held on this device are automatically overwritten and encrypted.



Preserving privacy is essential for your printing environment. The new KYOCERA TASKalfa 3253ci offers you superior security features as standard to safeguard your organisation.

TASKalfa^{*}

GENERAL

Technology: KYOCERA TASKalfa Laser Colour, HyPAS solution platform
Touch panel size: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel mounted

Engine speed (pages per minute): Up to 32/16 ppm A4/A3 in colour and black and white; Duplex print speed: 32

ppm A4; Duplex copy speed: 32 ppm, A4 **Resolution:** 4800dpi equivalent x 1200dpi (print) 600 x 600 dpi (scan/copy)

Warm-up time from power on: Approx. 18 seconds or less Time to first print: Approx. 5.9 / 7.7 seconds or less in black and white / colour

Time to first copy: Approx. 6.3/ 8.5 seconds or less in black and white / colour (DP), Approx. 5.3/ 7.0 seconds or less in black and white / colour (Platen)

CPU: Freescale QorlQ T1024 (Dual Core) 1.0GHz Memory: Standard 4GB RAM + 32GB SSD, Max 4GB RAM + 32GB SSD + 320GB HDD

32GB SSD + 320GB HDD

Standard interface: USB 3.0 (Super-Speed USB), 4 x USB
Host Interface, Gigabit Ethernet
(10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec,
802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 2
eKUIO slots, for optional internal print server or for
optional fax system, slot for optional Wireless LAN, Slot
for optional SD Card, NFC tag
Dimensions (W x D x H): Main unit: 602 x 665 x 790 mm
Weight: Main unit: Approx. 90 kg
Power source: AC 220 V ~ 240 V, 50/60 Hz
Power consumption:

Power consumption: Printing: 580 W Copying: 580 W

Low power mode: 50 W Ready mode: 50 W Sleep mode: 0.7 W

Noise level (sound pressure level ISO ISO 7779 measurement distance of 1 meter): Copying/Printing: 64 dB(A) Stand by: 35 dB (A)

Safety standards: 65, TÜV, CE.
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: Multipurpose tray: 150 sheets, $52-300 \text{ g/m}^2$ (Banner $136-163 \text{ g/m}^2$), A6R – SRA3 ($320 \times 450 \text{ mm}$), Custom (98

136 – 136 g/m², AGK – 3KA (320 K490 min), Custom (98 x 148 to 297 x 457.2 mm), Banner max. 304.8 x 1,220 mm; Tab paper (136 – 256 g/m²), Banner max. 304.8 x 1,220 mm; Standard universal paper cassette, 2 x 500 sheets, 52 – 300 g/m², upper cassette A6R up to A4R, lower cassette A6R up to SRA3,

Max. input capacity with options: 7,150 sheets A4 Duplex unit: Duplex as standard supports

A6R – SRA3, 64 – 256 g/m²

Output capacity: Standard 500 sheets face-down, max.

output capacity 4,300 sheets

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open

Operating systems: All current Windows operating systems, Mac OS X version 10.9 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing,

e-mail printing, WSD print, secure printing via SSL, IPsec,SNMPv3, quick copy, proof and hold, private print, job storage functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

Max. original size: A3 / Ledger Continuous copying: 1–9999 Zoom range: 25 –400% in 1% steps Preset magnification ratios: 5R/5E Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo, Diagram/map

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy

SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB, Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD scan

Scan speed: 180 images per minute (300 dpi, A4, with DP-7130) in black and white and colour

Scan resolution: 600dpi x 600dpi, 400dpi x 400dpi, 200dpi x 400dpi, 300dpi x 300dpi, 200dpi x 200dpi, 200dpi x 100dpi in A4; 256 greyscales per colour

Max. scan size: A3, Ledger
Original recognition: Text, photo, text + photo, Light Text /
Fine Line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(option), MS Office file(option)

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps Transmission speed: Max. 3 seconds (JBIG) Scanning speed: 2.0 seconds or less Maximum original size: A3, Banner max. 1,600 mm Compression method: JBIG, MMR, MR, MH Features: Network faxing, rotate transmission rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internet-fax, dual fax with second fax

CONSUMARI ES

Average continuous toner yield in accordance with 5%

TK-8335K Toner-Kit: Toner black for 25,000 pages A4
TK-8335K, TK-8335M, TK-8335Y Toner-Kits: Toner cyan, magenta, yellow for 15,000 pages
WT-8500 Waste Toner Bottle: 40,000 sheets (in accord

ance with 5% coverage black and white:colour = 7:3) Staple cartridge: SH-10 5000 x 3 staples for DF-7100, DF-7120 and BF-730 SH-12 5000 x 3 staples for DF-7110

OPTIONS

Fax System 12 Internet Fax Kit (A)
Scan Extension Kit (A):

Scan to searchable PDF solution (embedded OCR),

convert to PDF or MS Office (docx, xlsx, pptx)

Printing System 15: Fiery Controller

Printing System Interface Kit 15: Interface board for Fiery

Paper handling
DP-7100 Document processor: (Reversing), 140 sheets,
35 – 160 g/m² (simplex), 50 – 120 g/m² (duplex),

53 – 100 g/m² (simiplex), 50-120 g/m² (duplex), A6R – Banner up to 1,900 mm **DP-7110 Document processor:** (one-path duplex scanning) 270 sheets at 50 - 80 g/m², 35 – 220 g/m² (simplex), 50 – 220 g/m² (duplex), A6R – A3, Banner up to 1,900 mm **DP-7120 Document processor:** (Reversing), 50 sheets, 45 – 160 g/m² (simplex), 50 – 120 g/m² (duplex) A5R – A3, Banner up to 1,900 mm

DP-7130 Document processor: (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50 - 80 g/m^2 , 35–220 g/m² (simplex), 50–220 g/m² (duplex), A6R–A3, Banner up to 1,900 mm

DT-730(B) Document tray

PF-7100 Paper feeder: 2x 500 sheets, 52 - 300 g/m²,

PF-7110 Paper feeder: 2x 1,500 sheets, 52 - 300 g/m², A4,

PF-7120 A4 side Deck: 3,000 sheets, 60 – 300 g/m², A4, B5 DF-7100 Inner finisher: 500 sheets A4, 52–300 g/m², A6R-SRA3, Stapling up to 50 sheets A4 or 30 sheets A3 at 3 positions

Dir-7110' Document finisher + AK-7110: Main tray: 4,000 sheets A4; Sub tray: 200 sheets A4, 52–300 g/m², AGR-SRA3, Stapling up to 65 sheets A4 or

52–300 g/m², A6x–5xA3, Stapling up to 65 Sheets A4 of 30 Sheets A3 at 3 positions **DF-7120* Document finisher + AK-7110:**1,000 sheets A4, 52–300 g/m², A6R – SRA3,

Stapling up to 50 sheets A4 or 30 sheets A3 at 3 positions

AK-7110 Attachment kit for DF-7110 and DF-7120: 100 sheets, 52-300 g/m², AGR - SRA3, *Bridge unit AK-7110 is required when using a finisher.

7110 is required when using a finisher.
PH-7C/PH-7D Punch unif for DF-7120 and DF-7110:
2-hole/4-hole/Swedish type, 60 – 256 g/m², A5R – A3
MT-730(B) Mailbox sorter for DF-7110:
7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m²
BF-730 Booklet and tri-folding unit for DF-7110

BT-/30 BOOKlet and tri-folding unit for DF-/710 Half-folding: 52–256 g/m², A3, B4, A4R
Booklet: Max. 16 sheets (64 pages, 60–90 g/m²)
Non-staple folding: Max. 5 sheets (60–90 g/m²)
Tri-folding: Max. 5 sheets (60–90 g/m², A4R)
Multi tri-folding: 5 sheets (60–90 g/m²), 3 sheets
(91–105 g/m²)

JS-7100 Job separator: 100-sheet internal job separator, 52 – 300 g/m², ASR – SRA3 PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher/ wedish type

Banner Guide 10: Banner paper feeding guide, 10 sheets

Storage: HD-12: HDD 320 GB Keyboard Holder 10

NK-7120 Numeric keypad
USB IC Card Reader + Card Authentication Kit (B):
Support for various authentication keys available. The
card holder is standard

UG-33 AC: ThinPrint support

UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630)

Optional interface

IB-35: Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1.000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

Platen cover (E)
CB-7100W: Wooden cabinet CB-7110M: Metal cabinet

















KYOCERA Document Solutions (UK) Ltd, Eldon Court, 75-77 London Road, Reading RG15BS Tel: 0118 931 1500, Fax: 0118 931 1108 www.kyoceradocumentsolutions.co.uk, info@duk.kyocera.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

