

Compact, fast and reliable.

The TASKalfa 352ci is an all-round A4 colour MFP for small to medium size workgroups or front offices in any businesses where a compact size on a desk or under the desk and quick, productive and efficient operations are required.



TASKalfa 352ci



A4 Colour Multifunctional

35 ppm in Colour/Monochrome

1,200 x 1,200 dpi resolution

Specifications

GENERAL

KYOCERA TASKalfa Laser Colour Multifunctional, HyPAS™ solution platform
Operation panel: 177.8 mm (7 inch) full-colour touch panel display, speaker for job notification, 10–20° swivel mounted
Engine speed: Up to 35 pages A4 per minute, Duplex print/copy speed: 17 pages A4 per minute
Resolution: 1,200 × 1,200 dpi print at reduced speed, 600 × 600 dpi (scan/copy)
Warm-up time: Approx. 25 seconds or less
Time to first print: Approx. 6/7.5 seconds or less in Monochrome/Colour
Time to first copy: Approx. 8.5/10 seconds or less in Monochrome/Colour (Platen)
CPU: ARM Cortex-A9 Dual core 1.2GHz + ARM Cortex-M3 100MHz
Memory: Standard 1GB, max. 3GB + 128GB SSD
Standard interfaces: USB 2.0 (Hi-Speed), 2 × USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPsec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 1 eKUIO slot for optional internal print server or SSD hard disc, slot for optional SD Card
Integrated accounting: 100 department codes
Dimensions (W × D × H): 480 mm × 577 mm × 619.5mm
Weight: Approx. 36.5kg
Power source: AC 220–240V, 50/60Hz
Power consumption: Print Mode: 532W; Copy Mode: 547W; Ready Mode: 84W; Sleep Mode: 0.6W
Noise (sound pressure level: ISO 7779/ISO 9296): Ready Mode: 29.6dB(A) L_{PA}
Printing Mode (Mono/Colour): 50.3/50.4dB(A) L_{PA}
Safety standards: TÜV/GS, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11mm. Please use paper recommended by Kyocera under normal environmental conditions.
Input capacity: Multi-purpose tray: 100 sheets, 60–220g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (70 × 148 to 216 × 356mm);
Standard universal paper cassette: 250 sheets, 60–163g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (105 × 148 to 216 × 356mm);
Max. input capacity with options: 1,850 sheets A4
Duplex: Duplex as standard supports 60–163g/m², A4, A5, B5, Letter, Legal
Document Processor: Dual scan document processor as standard. 100 sheets, 50–120g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 × 148 to 216 × 356mm)
Output capacity: Max. 250 sheets face-down with paper full sensor

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc
Emulations: PCL6 (PCL-XL/PCL-5c), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print
Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Unix, Linux, as well as other operating systems on request
Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)
Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality
Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Wi-Fi Direct, Google cloud print

COPY FUNCTIONS

Max. original size: A4/Legal
Continuous copying: 1–9,999
Zoom range: 25–400% in 1% steps
Preset magnification ratios: 7 Reductions/5 Enlargements
Exposure mode: Auto, manual: 9 steps
Image adjustments: Text + Photo, Photo, Text, Map, Printed document
Features: Scan-once-copy-many, electronic sort (collate), ID card copy, Zin1, 4in1, auto cassette change, Skip blank page

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0, Scan-to-USB Host, Local/Network TWIN, WIA, WSD scan
Scan speed: 62ipm (300 dpi, A4, monochrome, duplex), 46ipm (300 dpi, A4 colour, duplex), 60ipm (300 dpi, A4, monochrome), 40ipm (300 dpi, A4 colour)
Scan resolution: 600, 400, 300, 200 dpi, 256 greyscales per colour
Max. scan size: A4, Legal
Original recognition: Text, photo, text + photo, light text/fine line, optimised for OCR
File types: TIFF, PDF, PDF/A, JPEG, XPS, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, MS Office file and Searchable PDF (optional Scan Extension Kit(A) is required)
Compression method: MMR/JPEG
Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

FAX FUNCTIONS

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6kbps
Transmission time: Max. 3 seconds (JBIG)
Scanning speed: 2.0 seconds or less

Address book: 200 entries (Personal), 50 entries (Group)

Fax resolution:

Normal: 8 dot/mm × 3.85 line/mm (200 × 100 dpi)
Fine: 8 dot/mm × 7.7 line/mm (200 × 200 dpi)
Superfine: 8 dot/mm × 15.4 line/mm (200 × 400 dpi)
Ultrafine: 16 dot/mm × 15.4 line/mm (400 × 400 dpi)
Half-tone: 256 greyscales

Maximum original size: A4/Legal

Compression method: JBIG, MMR, MR, MH

Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with 5% coverage A4.

TK-5345K Toner Kit: Microfine toner black for 17,000 pages A4

TK-5345C, TK-5345M, TK-5345Y Toner Kit: Microfine toner cyan, magenta, yellow for 9,000 pages A4

(Capacity of starter toner is black 6,000 pages, cyan, magenta, yellow 3,000 pages A4)

Staples: SH-13 for MS-5100, 2 × 1,500

OPTIONS

PF-5100 Paper feeder: (max. 3 units) 500 sheets, 60–220g/m², A4, A5, B5, Letter, Legal, Folio, Custom (92 × 162mm to 216 × 356mm)
MS-5100/MS-5100 B stapler: 20 sheets, one position semi-automatic stapling, includes 1,500 staples

Data Security Kit (E)

Memory upgrade: MD3-1024, MDDR3-2G, DDR3, 1GB/2GB

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B):

Supports various authentication card keys

IC Card Reader Holder 10: To integrate the USB IC Card

Scan Extension Kit (A): Scan to searchable PDF solution, (embedded OCR)

Optional interfaces:

IB-36*: Direct Wi-Fi Interface, Wireless LAN interface (802.11b/g/n)

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT (RJ45)

IB-51: Wireless LAN (802.11b/g/n)

HD-6 SSD: 32 GB for easy document management

HD-7 SSD: 128 GB for easy document management

CB-5100H Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 50cm (W × D × H)

CB-5100L Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 37cm (W × D × H)

CB-5100H Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 50cm (W × D × H)

CB-5100L Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 37cm (W × D × H)

CB-5100H Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 50cm (W × D × H)

CB-5100L Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 37cm (W × D × H)

CB-5100H Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 50cm (W × D × H)

CB-5100L Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 37cm (W × D × H)

CB-5100H Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 50cm (W × D × H)

CB-5100L Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 37cm (W × D × H)

CB-5100H Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 50cm (W × D × H)

CB-5100L Cabinet: Wooden desk with storage capacity, approx. 39cm × 53cm × 37cm (W × D × H)

* IB-36 can be installed independently from IB-50/51 or SSD

The TASKalfa 352ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 352ci provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

HyPAS™



KYOCERA Document Solutions Partner

JANUARY2020DSTASKALFA352CI/VER1.0

KYOCERA Document Solutions Europe B.V.
Bloemlaan 4, 2132 NP Hoofddorp, The Netherlands
Tel +31 (0) 20-654-0000 – Fax +31 (0) 20-653-1256



kyoceradocumentsolutions.eu

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.