

**RICOH**  
imagine. change.





# MP W7100SP/MP W8140SP

## GENERAL

Configuration:	Console
Copying/printing process:	Electro-photographic printing
Paper source: standard:	2 Roll paper feeder
Paper source: optional:	2 Roll paper feeder 250 sheets x 2 drawer paper cassettes
Resolution:	600 x 600 dpi
Grayscale printing:	2 levels
Zoom:	25% to 400% by 0.1% increments
Cutting method:	Preset size cut Synchronised cut Variable cut
Hard Disk Drive:	320 GB (shared with copier/ printer/scanner)
Power source:	208 - 240 V, 15 A (max.), 60/Hz
Dimensions (W x D x H):	1,250 x 755 x 1,193 mm 49.2 x 29.7 x 47"
Weight:	287/295 kg 631.4/649 lbs.

## COPIER

Copy modes:	Text, Text/Photo, Photo, Drawing, Generation Text, Generation Photo, Pasted Original, Background Line, Highlighter
Copier features:	Auto Paper Selection (APS), Document Server, Auto Reduce/Enlargement, User Auto Reduce/Enlargement, Preset Reduce/Enlargement, Zoom, Size Magnification, Directional Magnification, Directional Size Magnification (percentage and mm/inch), Fine Magnification, Electronic Sort, Image Overlay, Format Overlay, Negative/Positive, Mirroring, Double Copy, Repeat Copy, Sample Copy, Combine Images, Job Interrupt, User Code, Key Operator Code, Job Program (up to 10 jobs), Margin Adjustment - 0 to 200 mm (by 1 mm steps), Image Shift - Front/Rear/Left/Right (0 to +/- 200 mm by 1 steps), Unprintable Margins - 5 mm (lead edge, trail edge, each side), Edge Erase, Preset Stamps, User Preset Stamps, Date Stamp, Page Stamp, Auto Off, Energy Saver Mode, Auto Start

## PRINTER

Controller board:	Embedded
CPU:	1.06 GHz
Print speed:	10/14 ppm D-size LEF 5/7 ppm E-size SEF
Print resolution:	Up to 600 dpi
Print drivers:	Adobe Postscript HDI
Supported file formats:	HP-GL, HP-GL2, HP-RTL, TIFF, CALS, JPEG, PostScript, PDF, Microsoft Office, DWG/DWF
Fonts:	European 136 fonts (PS3)
Network interface: standard:	100 base-TX/10 base-T Ethernet USB 2.0
Network interface: optional:	Wireless LAN IEEE 802.11a/g/n
Network protocol: standard:	TCP/IP (IPv4, IPv6)
Network protocol: optional:	IPX/SPS
Supported OS:	Windows® XPMista/7/8.1/ 2003 Server/2008 Server/ 2008R2 Server/2012 Server/2012R2 Server Mac® OS (10.7 or later)
Media to print:	Yes (JPEG/TIFF/PDF)
Printer features:	Sample Print, Locked Print, Hold Print, Stored Print, Store and Print, Unauthorized Copy Prevention, One Direction, WSD Printer, Color Matching, POP, CUD, PDF Direct Print
Supported languages:	English, Brazilian Portuguese, Danish, Dutch, Finnish, French, German, Italian, Japanese, Korean, Norwegian, Polish, Romanian, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese, Turkish

## SCANNER

Color scan:	Standard
Scan to multimedia:	Standard
Media to print:	Standard
Scan speed: colour:	200 mm/s or 0 ips (600 dpi)
Scan speed: BW:	340 mm/s (600 dpi)
Scan resolution:	150 - 600 dpi TWAIN: up to 1,200 dpi
Scan modes: colour:	Text/Photo Photo
Scan modes: BW:	Text Text/Photo Text/Line Art (default) Photo Drawing Text/Drawing Grayscale
Scan detection:	Auto Detect Preset Paper Size Custom Size
Scan protocols:	Network: TCP/IP Scan to email: SMTPPOP before SMTP Scan to folder: SMBFTPNC
Image density:	9 levels of lighter to darker
Edit:	Erase Border Positive/Negative Mirror Image
Scanner features:	Scan-to-Email (SMTP), Scan-to-Folder (SMB, FTP), Scan-to-URL, Scan-to-USB/SD, Network TWAIN, Scan-to-NCP, Scan-to-Document Server, Authentication Modes, Image Rotation, Contrast Setting Integrated, Continuous Input, Invert, Multiple Scan Settings, Reading Area Setting, RGB (24-bit), Grey, B/W
Preview:	Full view: 18 x 24" Section preview: 36 x 48"
File formats:	Multi page TIFF, Single page TIFF, Multi page PDF, Single page PDF, Single page JPEG, High Compression PDF, PDF/A

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice.

The colour of the actual product may vary from the colour shown in the brochure.

The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2022 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

**RICOH**  
imagine. change.

## ECOLOGY

Maximum power consumption: 2.4/3.5 kW per hour

For availability of models, options and software, please consult your