

TOSHIBA

e-STUDIO[™]2521AC

Big and better changes for small workgroups start with the e-STUDIO2521AC. Protecting data with elevated security, this MFP integrates multiple features into one dynamic device, so your team can perform a variety of tasks effortlessly.

- Up to 25 PPM
- Compact Design
- Feature Rich
- Advanced Security Options
- Environmentally Friendly



Main Specifications

Copy System	Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	25 PPM (LT)
First Copy Out	Color: Less Than 9.5 Seconds Monochrome: Less Than 7.1 Seconds
Warm-Up Time	From powering on: Approx. 21 Seconds From Sleep & Low Power: Less Than 15 Seconds
Copy Resolution	600 × 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 11" x 17", Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 350 Sheets/Max. 2,900 Sheets
Original Feed	100-Sheet RADF
Max. Original Size	LD/A3
Paper Feed Sizes	Drawer 1: 250 Sheets-ST-R to LD Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to LD Opt. PFU: 550 Sheets-ST-R to LD Opt. 550-Sheet Paper Feed Pedestal-ST-R to LD Opt. 550-Sheet Drawer for PFP-ST-R to LD Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 250 Sheets-16lb Bond-90lb Index Stack Feed Bypass: 100 Sheets-16lb Bond-90lb Index Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-90lb Index Opt. 550 Sheets Drawer for PFP-16lb Bond-90lb Index Opt. Envelope Cassette for PFP-16lb Bond-90lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17lb-90lb Index Standard Automatic Duplex Unit (16lb Bond-90lb Index)
Paper Weights	25% to 400% Max. 84K Month (Color: 100%) Max. 84K Month (Monochrome: 100%) Approx.131lb
Duplex	26" (W) x 23" (D) x 31" (H)
Reproduction Ratio	CMY: 38K, K: 39.8K @ 5%
Max Duty Cycle	120 Volts, 50/60 Hz, 12 Amps
Weight	Maximum 1.5kW (120V)
Approx. Dimensions	NEMA 5-15
CMYK Toner Yield	4GB
Power Source	128GB Solid State Drive (SSD)
Power Consumption	
Plug Type	
Memory	
Hard Disk Drive	

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 × 600 dpi, 1,200 × 1,200 dpi or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows® 8.1,10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell®
Printing Protocols	Environments, EtherTalk for Macintosh Environments SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD
Print Drivers	w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed)
Wireless Device	Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Device Management	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Account Control	TopAccess Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist



Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/ IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication
*Conformance with HCD-PPv1.0 in High Security Mode
ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

Scan Specifications

Scan Speed	RADF Scan: Up to 73 IPM (Monochrome or Color)
Scan Weights	DSDF Simplex or Duplex: 9.3-110lb Bond RADF Scan: Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
OCR	DOC/XLS/PPT/PDF
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX, Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options		
RADF	MR3033	e-BRIDGE Job Point GB1560NODE
Platen Cover	KA5005PC	e-BRIDGE Job Separator GB1590NODE
Additional Paper Options		
Paper Feed Unit	MY1051	e-BRIDGE Job Build GB1610NODE
Paper Feed Pedestal	KD1072	e-BRIDGE Plus for OneDrive GB2300NODE
Drawer Module	MY1052	e-BRIDGE Plus for SharePoint GB2310NODE
Envelope Cassette Option	MY1053	e-BRIDGE Plus for Exchange GB2320NODE
Large Capacity Feeder	KD1073LT	Workplace Productivity Bundle GB2330NODE
Finishing Options		
50-Sheet Inner Finisher	MJ1048	e-BRIDGE Plus for Gmail GB2380NODE
Hole Punch for MJ1048	MJ6011	e-BRIDGE Plus for Google Workspace GB2390NODE
Job Separator	MJ5014	Hardcopy Security Printing GP1190NODE
Connectivity/Security Options		
FAX Unit/2 nd Line for FAX Unit	GD1370N	Security SSD (512GB) GE1280
Wireless LAN/Bluetooth	GN4030A3	FIPS SSD (512GB) GE1350
Fax Over IP License Key	GS1100NODE	e-BRIDGE Plus GB2540NODE
Bluetooth Keyboard	GR9001	e-BRIDGE Global Print GB2550NODE
2 nd NIC Holder	GR1430	Miscellaneous Options
USB Hub	GR1420	Card Reader Holder GR1320
Meta Scan Enabler	GS1010NODE	Accessory Tray GR1330
External Interface Enabler	GS1020	Panel 10-Key Option GR1340
IPSec Enabler	GP1080NODE	Stand STAND5015
Unicode Font Enabler	GS1007NODE	Work Tray KK5005
Multi-Station Print Enabler		Manual Pocket KK5008
Per Seat License	GS1090NODE	Harness for Coin Controller GQ1280
e-BRIDGE Replicator	GB1550NODE	Accessible Arm KK2560

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

business.toshiba.com