

Xerox[®] VersaLink[®] C505 Colour Multifunction Printer

VersaLink® C505 Colour Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.co.uk.



SYSTEM SPECIFICATIONS	VERSALINK® C505	
One-sided Speed ¹ 216 x 279 mm A4/210 x 297 mm 216 x 356 mm	Up to 45 ppm colour and black-and-white Up to 43 ppm colour and black-and-white Up to 37 ppm colour and black-and-white	
Two-sided Speed ¹ 216 x 279 mm A4/210 x 297 mm 216 x 356 mm	Up to 44 ppm colour and black-and-white Up to 42 ppm colour and black-and-white Up to 22 ppm colour and black-and-white	
Monthly Duty Cycle ²	Up to 120,000 pages/month	
Recommended Average Monthly Print Volume ³	Up to 10,000 pages	
Hard Drive	320 GB HDD	
Processor	1.05 GHz ARM Dual-Core	
Memory	4 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North Americα	Voltage: 110-127V +/-10 % Frequency: 50/60 Hz +/-3 %, 12A			
Europe and Other Geographies	Voltage: 220-240V Frequency: 50/60 H			
POWER CONSUMPTION	1			
Continuous Printing ⁴	730 watts or less			
Ready/Standby Mode ⁴	89 watts or less			
Energy Saver/Sleep Mode ⁴	0.9 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	0 to 35 ℃			
Required Temperature Range (Operating)	10 to 32 °C			
Required Relative Humidity	15% to 85%			
Sound Power Levels Operating Standby	7.17 B(A) or less 4.9 B(A) or less			
Sound Pressure Levels Operating Standby	56.2 dB(A) or less, 33.6 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 65 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersαLink [®] C505	470 mm	502.8 mm	643.7 mm	35 kg
550-sheet Paper Tray	420 mm	464.5 mm	123 mm	6.6 kg
High-Capacity Feeder (includes Caster Base)	724.2 mm	772.1 mm	459 mm	19.7 kg
Cabinet (includes Caster Base)	724.2 mm	772.1 mm	336 mm	16.6 kg
Caster Base	724.2 mm	772.1 mm	90 mm	8.5 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersαLink® C505	594 mm	655 mm	789 mm	43 kg
550-sheet Paper Tray	535 mm	584 mm	248 mm	8.5 kg
High-Capacity Feeder (includes Caster Base)	568 mm	663 mm	711 mm	38 kg
Cabinet (includes Caster Base)	584 mm 629 mm 597 mm 28 kg			
Caster Base	585 mm 619 mm 330 mm 18 kg			
CERTIFICATIONS		•	•	•
	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			

PRINT			
First-Print-Out Time	As fast as 5.6 seconds colour/5.1 seconds black-and-white		
Print Resolution	Up to 1200 x 2400 dpi		
Page Description Languages	PCL [®] 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe [®] PostScript [®] 3 [™]		
Maximum Print Area	4 mm from edge of paper		
Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Colour Correction Colour Adjustments (lightness, contrast, saturation, colour balance) Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings		
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A		
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.		
Fonts	PostScript fonts: 136 PCL fonts: 83		

Xerox® VersaLink® C505 Colour Multifunction Printer

Xerox® Globαl Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management.		
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.		
COPY			
Document Scanner	100-sheet Single-Pass Duplex Automatic Document Feeder (DADF)		
Document Scanner Size	Platen: Up to 216 x 356 mm DADF: Up to 216 x 356 mm		
Simplex Copy Speed	Up to 45 cpm (copies per minute) 216 x 279 mm Up to 43 cpm A4/210 x 297 mm		
Duplex Copy Speed	Up to 45 cpm (copies per minute) 216 x 279 mm Up to 43 cpm A4 (210 x 297 mm)		
First-Copy-Out Time	As fast as 6.6 seconds colour/4.9 seconds black-and-white		
Sides (input: output)	1:1, 1:2, 2:2 and 2:1		
Quantity	1 to 999		
Resolution (max.)	Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments		
Concurrency	Concurrent scanning and printing		
Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping) including font format, colour and style options* Auto-colour Sensing Automatic Background Suppression Book Copying with Centre Erase Booklet Copying* Collation Colour Balance Colour Balance Colour Effects Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten/Darken N-up Original Orientation Original Size Original Type Page Layout Reduce/Enlarge 25% to 400% Sample Copy Saturation Sharpness *Requires HDD/Productivity Kit		

SCAN		
Capability	Black-and-white and colour scanning	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Simplex Input Speed	Black-and-white: Scan up to 43 ipm 216 x 279 mm/40 ipm A4 Colour: Scan up to 42 ipm 216 x 279 mm/40 ipm A4	
Duplex Input Speed	Black-and-white: Scan up to 73 ipm 216 x 279 mm/69 ipm A4 Colour: Scan up to 55 ipm 216 x 279 mm/52 ipm A4	
Resolution	Optical – 600 x 600 dpi	
Bit Depth	24-bit colour/8-bit greyscale	
Maximum Scan Area	Platen: Up to 216 x 356 mm Document Feeder: Up to 216 x 356 mm	
Network Filing Protocols	FTP SMTP SMB sFTP	
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A	
Scan Driver Compatibility	WIA TWAIN	
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)	
NETWORK SCANNING – SOFTW	ARE SOLUTIONS	
Xerox® ConnectKey Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.	
FAX ⁵		
Fax Speed	33.6 Kbps	
Memory	4 MB	
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi	
Compression	MH, MR, MMR, JBIG	
Fax Features	Walk-up Fax, LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)	
MOBILE SOLUTIONS AND MOBI	LE DEVICE APPS	
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Mopriα [®] Certified	ConnectKey® Technology-enabled print devices are Mopria certified. Mopria certification ensures you can print wirelessly from your Mopria-supported (Android) smart phone, tablet and other mobile devices instantly and easily.	

(compale, phone, tablet, 105, Android*, Grouple* Chromebook* and minor) to a Xerax® Piniter or Muturbuncton Printer using a single email address with no Til Intervention. No training is needed. End users simply send attachments to the email address and release them at the panel of the muturbuncton printer. Third Service Plug-in for undroid* (Free at since) the printer of the muturbuncton printer of the muturbuncton printer or the printer of the printe			
printing without third party apps or additional print drivers. You can easily print photos, who pages include Play™ Store) and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two sided printing, stopling and secure code release. A fixe download is available from the Google Play™ store. The Xerox® Easy Assist App The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-apport services and teal-time monitoring of printer performance. And, Xerox® Smart Software takes the guess work out of setup by auditomating the installation of the lettes software of your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly. Xerox® Workplace Suite and Xerox® Workplace Suite is a modular set of workflows designed to some customers time and money by providing effective control over their print fleet software of your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly. Xerox® Workplace Cloud Xerox® Workplace Suite and Suite is a modular set of workflows designed to some customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an an premises sever version (Workplace Suite) and with a cloud based version (Workplace Suite). **ECCURITY** **ECURITY** **Access Controls** **Access Controls** **Access Controls** **Access Controls** **Access Controls** **Ac	Xerox [®] @printbyXerox App	(computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® Printer or Multifunction Printer using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the panel of the	
MFP right from your mobile phone. It provides easy access to self-support services and red-lime monitoring of printer performance. And, Xerox® Smart Stats Ostware takes these work out of setup by automating the installation of the latest software for your printer or MFP on your computer—all without IT support—allowing you to be up and running quickly. Xerox® Workplace Suite and Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robusts workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Suite) and with a cloud based-version (Workplace Suite). ECURITY **Recurity Features** **Access Controls** **Access Con	Print Service Plug-in for Android™ (Free at Google Play™ Store)	printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code	
security Features Access Controls AES 256-bit encryption Audit Log Certificate Peath Vollation Detection of External Program Falsification (XCP plug-in) Demonin Filtering Fip 140-2 Firmware Verification Detection of External Post Pre- Immage Pre- Installed Self-Signed Certificates Role Based Permissions Secure Print Secure Part Secure Print Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/NET) SNNPy3 TIS 13/SSL Tristed Platform Module (TPM) "Requires HDD/Productivity Kit CCOUNTING Copy, Print, Fax, Scan and Email usage Copy, Print, Fax, Scan and Email usage Copy Print Print Print Print P	Xerox [®] Easy Assist App	MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your	
Access Controls AES 256-bit encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Cisco® Identity Services Engine (ISE) Integration Detection of External Program Falsification (XCP plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure First Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/NET) SNNP/P3 TLS 1.3/SSL Trusted Platform Module (TPM) *Requires HDD/Productivity Kit **CCOUNTING** **CCO	Xerox® Workplace Suite and Xerox® Workplace Cloud	by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version	
AES 256-bit encryption Audit Log Certificate Path Validation Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Clacco Identity Services Engine (ISE) Integration Detection of External Program Falsification (XCP plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Final Secure Fax Secure Pinal Secure Fax Secure Pinal Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPy3 ILS 1.3/SSL Trusted Platform Module (TPM) *Requires HDD/Productivity Kit ***CCOUNTING** ***	SECURITY		
ACCOUNTING (SEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD) Tracking Copy, Print, Fax, Scan and Email usage Accounting Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)	Security Features	AES 256-bit encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Cisco® Identity Services Engine (ISE) Integration Detection of External Program Falsification (XCP plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 TLS 1.3/SSL Trusted Platform Module (TPM)	
Tracking Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 60,000 Account IDs with HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)	ACCOUNTING	requires IDD/Ploductivity hit	
Copy, Print, Fax, Scan and Email usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)		NG/NETWORK ACCOUNTING (STANDARD)	
Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)			
Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)	Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD	
Features Administrator can manage the feature via the Embedded Web Server.		Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD	
	Features	Administrator can manage the feature via the Embedded Web Server.	

ACCOUNTING OPTIONS	5 – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third-party server, enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account	
PAPER HANDLING		
DOCUMENT FEEDER		
Capacity ⁶	Single-Pass Duplex Automatic Document Feeder (DADF): 100 sheets	
Sizes	Custom sizes: 140 x 140 mm to 216 x 356 mm	
Weights One-sided: Two-Sided:	60 to 128 gsm 60 to 128 gsm	
BYPASS TRAY		
Capacity ⁶	150 sheets	
Sizes	Custom sizes: 76 x 127 mm to 216 x 356 mm	
Weights One-sided: Two-Sided:	60 to 220 gsm 60 to 176 gsm	
Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Card Stock Pre-Printed Recycled	
TRAY 1		
Capacity ⁶	550 sheets	
Sizes	Custom sizes: 76 x 190 mm to 216 x 356 mm	
Weights One-sided: Two-Sided:	60 to 220 gsm 60 to 176 gsm	
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Card Stock Heavyweight Cardstock Pre-Printed Recycled Envelope	

UP TO FOUR ADDITIONAL TRAYS	5 (OPTIONAL)		
Capacity ⁶	550 sheets		
Sizes	Custom sizes: 76 x 190 mm to 216 x 356 mm		
Weights One-sided: Two-Sided:	60 to 220 gsm 60 to 176 gsm		
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Card Stock Heavyweight Cardstock Pre-Printed Recycled		
•	EET TRAY CAN BE ADDED TO HIGH-CAPACITY FEEDER)		
Capacity ⁶	2,000 sheets		
Sizes	A4		
Weights One-sided: Two-Sided	60 to 176 gsm 60 to 176 gsm		
Types	Bond Plain Paper Hole Punched Letterhead Lightweight Card Stock Pre-Printed Recycled		
TOTAL CAPACITY			
Standard Device Capacity ⁶	700 sheets		
Total Device Capacity ⁶	3,250 sheets		
PAPER OUTPUT			
Output Capacity ⁶	400 sheets		
Automatic Two-sided Printing	Standard		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS		
REMOTE CONTROL PANEL			
	 Enables faster, more convenient technical support and user training IT administrators and other authorised users can control the device remotely from a web page on any device Remote user experience is identical to performing tasks directly at the device 		

XEROX® CENTREWARE® WEB SOF	TWARE		
	 A web-based server application for network administrators that permits web-browser-based device management from any workstation, whether running Windows, UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
XEROX® EMBEDDED WEB SERVER	R – INTEGRATED DEVICE WEB PAGE		
Device Status	 Tray Status/Contents Consumables Status Billing/Usage Quick Links Online Support 		
Print Queue Viewing	Job print queue management — view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™		
REMOTE SERVICES			
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
WHAT'S IN THE BOX			
	VersaLink® C505 Colour Multifunction Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 2,400 print capacity ⁷ , Black: 5,000 print capacity ⁷ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers and Warranty Statement) Installation Guide Quick Use Guides Power Cord Fax Cord		

Xerox® VersaLink® C505 Colour Multifunction Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Black: 5,000 standard pages ⁷ Cyan: 2,400 standard pages ⁷ Magenta: 2,400 standard pages ⁷ Yellow: 2,400 standard pages ⁷	106R03862 106R03859 106R03860 106R03861
High Capacity Toner Cartridges	Black: 12,100 standard pages ⁷ Cyan: 5,200 standard pages ⁷ Magenta: 5,200 standard pages ⁷ Yellow: 5,200 standard pages ⁷	106R03876 106R03870 106R03871 106R03872
Extra-High Capacity Toner Cartridges	Cyan: 9,000 standard pages ⁷ Magenta: 9,000 standard pages ⁷ Yellow: 9,000 standard pages ⁷	106R03873 106R03874 106R03875
ROUTINE MAINTENANCE ITEMS		
Drum Cartridges	Cyan: 40,000 pages ⁸ Magenta: 40,000 pages ⁸ Yellow: 40,000 pages ⁸ Black: 40,000 pages ⁸	108R01481 108R01482 108R01483 108R01484
Waste Cartridge	30,000 pages ⁸	108R01416
ACCESSORIES		
550-sheet Feeder		097S04949
2,000-sheet High-Capacity Feeder (includes Caster Base)		097S04948
Stand (includes stabilisers)		097S04994
Caster Base		097S04954
Productivity Kit with 320 GB HDD		497K18360
Wireless Network Adapter (Wi-Fi Kit)		497K16750

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.



<sup>Declared print speed in accordance with ISO/IEC 24734.

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

Requires analogue phone line.

Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks

Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf.</sup>