

## Xerox<sup>®</sup> VersaLink<sup>®</sup> C605 Colour Multifunction Printer

VersaLink® C605 Colour Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.co.uk.



SYSTEM SPECIFICATIONS	VERSALINK® 605
<b>One-sided Speed</b> <sup>1</sup> 216 x 279 mm A4/210 x 297 mm 216 x 356 mm	Up to 55 ppm colour and black-and-white Up to 53 ppm colour and black-and-white Up to 45 ppm colour and black-and-white
<b>Two-sided Speed</b> 216 x 279 mm A4/210 x 297 mm 216 x 356 mm	Up to 52 ppm colour and black-and-white Up to 50 ppm colour and black-and-white Up to 26 ppm colour and black-and-white
Monthly Duty Cycle <sup>2</sup>	Up to 120,000 pages/month
Recommended Average Monthly Print Volume <sup>3</sup>	Up to 17,000 pages
Hard Drive	320 GB HDD
Processor	1.05GHz ARM Dual-Core
Memory	4 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS	LECTRICAL REQUIREMENTS			
North America	Voltage: 110-127V +/-10 % Frequency: 50/60 Hz +/-3 %, 12A			
Europe and Other Geographies	Voltage: 220-240V +/- Frequency: 50/60 Hz +			
POWER CONSUMPTION	,			
Continuous Printing <sup>4</sup>	820 watts or less			
Ready (Standby) Mode <sup>4</sup>	90 watts or less			
Energy Saver (Sleep) Mode <sup>4</sup>	0.9 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	0 to 35° C			
Required Temperature Range (Operating)	10 to 32° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels Operating Standby	7.27 B(A) or less 4.84 B(A) or less			
Sound Pressure Levels Operating Standby	57.4 dB(A) or less 33.5 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 65 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	470 mm	503 mm	643.7 mm	36.1 kg
Base Unit with Mailbox	487.5 mm	503 mm	843.7 mm	44.1 kg
Base Unit with Finisher	487.5 mm	503 mm	843.7 mm	45.6 kg
Base Unit with High-Capacity Feeder and Finisher	724.2 mm	772.1 mm	1302.7 mm	65.3 kg
Base Unit with High-Capacity Feeder and Mailbox	724.2 mm	772.1 mm	1302.7 mm	63.8 kg
550-sheet Paper Tray	420 mm	464.5 mm	123 mm	6.6 kg
High-Capacity Feeder (includes Caster Base)	724.2 mm	772.1 mm	459 mm	19.7 kg
Cabinet (includes Caster Base)	724.2 mm 772.1 mm 336 mm 16.6 kg			
Caster Base	724.2 mm 772.1 mm 90 mm 8.5 kg			
Mailbox	450.8 mm 477.6 mm 248.0 mm 5.3 kg			
Finisher	450.8 mm	411.0 mm	248.0 mm	6.8 kg

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	594 mm	655 mm	789 mm	44 kg
550-sheet Paper Tray	535 mm	584 mm	248 mm	8.5 kg
High-Capacity Feeder (includes Caster Base)	568 mm	663 mm	711 mm	38 kg
Cabinet (includes Caster Base)	584 mm	629 mm	597 mm	28 kg
Caster Base	585 mm	619 mm	330 mm	18 kg
Mailbox	573 mm	518 mm	386 mm	7.8 kg
Finisher	573 mm	398 mm	386 mm	8.8 kg
CERTIFICATIONS				
	To view the latest list of a	certifications, go to www.x	erox.com/OfficeCertificat	tions.
PRINT				
First-Print-Out Time	As fast as 5.2 seconds colour/4.8 seconds black-and-white			
Print Resolution	Up to 1200 x 2400 dpi			
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
Maximum Print Area	4 mm from edge of paper			
Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) LAN Fax (requires Fax Kit) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings			
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A			

Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at https://www.support.xerox.com/en-gb.	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management.	
Xerox <sup>®</sup> Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	
COPY		
Document Scanner	100-sheet Single-Pass Duplex Automatic Document Feeder (DADF)	
Maximum Scan Area	Platen: Up to 216 x 356 mm DADF: Up to 216 x 356 mm	
Simplex Copy Speed	Up to 55 cpm (copies per minute) 216 x 279 mm Up to 53 cpm A4/210 x 297 mm	
Duplex Copy Speed	Up to 50 cpm (copies per minute) 216 x 279 mm Up to 47 cpm A4 (210 x 297 mm)	
First-Copy-Out Time	As fast as 6.7 seconds colour/4.8 seconds black-and-white	
Sides (input:output)	1:1, 1:2, 2:2 and 2:1	
Quantity	1 to 999	
Resolution (max.)	Up to 600 x 600 dpi	
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments	
Concurrency	Concurrent scanning and printing	

Copy Features	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping) including font format, colour and style options* Auto-colour Sensing Automatic Background Suppression Book Copying with Centre Erase Booklet Copying* Collation Colour Balance Colour Effects Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten/Darken N-up Original Orientation Original Size Original Type Page Layout Reduce/Enlarge 25 % to 400 % Sample Copy Saturation Sharpness	
SCAN	*Requires HDD/Productivity Kit	
Capability	Black-and-white and colour scanning	
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs	
Simplex Input Speed	Black-and-white: Scan up to 49 ipm 216 x 279 mm/46 ipm A4 Colour: Scan up to 47 ipm 216 x 279 mm/46 ipm A4	
Duplex Input Speed	Black-and-white: Scan up to 75 ipm 216 x 279 mm/71 ipm A4 Colour: Scan up to 55 ipm 216 x 279 mm/52 ipm A4	
Resolution	Optical – 600 x 600 dpi	
Bit Depth	24-bit colour/8-bit greyscale	
Maximum Scan Area	Platen: Up to 216 x 356 mm Document Feeder: Up to 216 x 356 mm	
Network Filing Protocols	FTP SMTP SMB sFTP	
File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearised PDF (set via embedded web server) and PDF/A	
Scan Driver Compatibility	WIA TWAIN	
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)	
NETWORK SCANNING – SOFTW	ARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.	

FAX <sup>5</sup>			
Fax Speed	33.6 Kbps		
Memory	4 MB		
Resolution	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi		
Compression	MH, MR, MMR, JBIG		
Fax Features	Walk-up Fax, LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)		
MOBILE SOLUTIONS AND MOB	ILE DEVICE APPS		
Apple <sup>®</sup> AirPrint <sup>®</sup>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.		
Xerox <sup>®</sup> @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® Printer or Multifunction Printer using a single email address with no IT intervention. No training is needed. End users simply send attachments to the email address and release them at the panel on the multifunction printer.		
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.		
Xerox <sup>®</sup> Easy Assist App	The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.		

SECURITY	
Security Features	Access Controls AES 256-bit encryption Audit log Certificate path validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Cisco® Identity Services Engine (ISE) Integration Detection of external program falsification (XCP plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 TLS 1.3/SSL Trusted Platform Module (TPM)
	*Requires HDD/Productivity Kit
ACCOUNTING	COLINITING (METHODY ACCOUNTING (STANDARD)
Tracking	COUNTING/NETWORK ACCOUNTING (STANDARD)  Copy, Print, Fax, Scan and Email usage
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts  Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server
ACCOUNTING OPTIONS	S – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)
	<ul> <li>Enhanced network accounting with up-to-the-minute data on how the system is being used</li> <li>Comprehensive management and enterprise-scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.co.uk</li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third-party server, enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third-party Networking Account</li> </ul>

PAPER HANDLING			
DOCUMENT FEEDER			
Capacity <sup>6</sup>	Single-Pass Duplex Automatic Document Feeder (DADF): 100 sheets		
Sizes	Custom sizes: 140 x 140 mm to 216 x 356 mm		
Weights One-sided: Two-Sided	60 to 128 gsm 60 to 128 gsm		
BYPASS TRAY			
Capacity <sup>6</sup>	150 sheets		
Sizes	Custom sizes: 76 x 127 mm to 216 x 356 mm		
Weights One-sided: Two-Sided	60 to 220 gsm 60 to 176 gsm		
Mediα Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled		
TRAY 1			
Capacity <sup>6</sup>	550 sheets		
Sizes	Custom sizes: 76 x 190 mm to 216 x 356 mm		
Weights One-sided: Two-Sided	60 to 220 gsm 60 to 176 gsm		
Mediα Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled Envelope		
UP TO FOUR ADDITIONAL TRAYS (OPTIONAL)			
Capacity <sup>6</sup>	550 sheets		
Sizes Weights One-sided:	Custom sizes: 76 x 190 mm to 216 x 356 mm  60 to 220 gsm		
Two-Sided	60 to 176 gsm		
Mediα Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled		

Capacity <sup>6</sup>	2,000 sheets		
Sizes	A4		
Weights One-sided: Two-Sided	60 to 176 gsm 60 to 176 gsm		
Media Types	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled		
TOTAL CAPACITY			
Standard Device Capacity <sup>6</sup>	700 sheets		
Maximum Device Capacity <sup>6</sup>	3,250 sheets		
PAPER OUTPUT/FINISHING			
Capacity <sup>6</sup>	Up to 400 sheets		
Automatic Two-sided Printing	Standard		
FINISHER			
Capacity <sup>6</sup>	500-sheet tray, 50-sheet stapling		
MAILBOX			
Capacity <sup>6</sup>	Four 100-sheet bins		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS		
REMOTE CONTROL PANEL			
	<ul> <li>Enables faster, more convenient technical support and user training</li> <li>IT administrators and other authorised users can control the device remotely from a web page on any device</li> <li>Remote user experience is identical to performing tasks directly at the device</li> </ul>		
XEROX® CENTREWARE® WEB S	OFTWARE		
	<ul> <li>A web-based server application for network administrators that permits web-browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>		

XEROX® EMBEDDED WEB S	ERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul> <li>Tray Status/Contents</li> <li>Consumables Status</li> <li>Billing/Usage</li> <li>Quick Links</li> <li>Online Support</li> </ul>	
Print Queue Viewing	Job print queue management – view and delete	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™	
REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
WHAT'S IN THE BOX		
	VersaLink® C605 Colour Multifunction Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 6,000 print capacity <sup>7</sup> , Black: 10,000 print capacity <sup>7</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers and Warranty Statement) Installation Guide Quick Use Guides Power Cord Fax Cord	

## Xerox® VersaLink® C605 Colour Multifunction Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER		
SUPPLIES				
Standard Capacity Toner Cartridges	Black: 6,000 standard pages <sup>7</sup> Cyan: 6,000 standard pages <sup>7</sup> Magenta: 6,000 standard pages <sup>7</sup> Yellow: 6,000 standard pages <sup>7</sup>	106R03899 106R03896 106R03897 106R03898		
High Capacity Toner Cartridges	Black: 12,200 standard pages <sup>7</sup> Cyan: 10,100 standard pages <sup>7</sup> Magenta: 10,100 standard pages <sup>7</sup> Yellow: 10,100 standard pages <sup>7</sup>	106R03907 106R03904 106R03905 106R03906		
Extra-High Capacity Toner Cartridges	Black: 16,900 standard pages <sup>7</sup> Cyan: 16,800 standard pages <sup>7</sup> Magenta: 16,800 standard pages <sup>7</sup> Yellow: 16,800 standard pages <sup>7</sup>	106R03935 106R03932 106R03933 106R03934		
ROUTINE MAINTENANCE ITEM	IS			
Drum Cartridges	Cyan: 40,000 pages <sup>8</sup> Magenta: 40,000 pages <sup>8</sup> Yellow: 40,000 pages <sup>8</sup> Black: 40,000 pages <sup>8</sup>	108R01485 108R01486 108R01487 108R01488		
Waste Cartridge	30,000 pages <sup>8</sup>	108R01416		
ACCESSORIES				
550-sheet Feeder		097S04949		
2,000-sheet High-Capacity Feed	er (includes Caster Base)	097S04948		
Cabinet (includes stabilisers)		097S04994		
Caster Base		097S04954		
Finisher (500 sheets, 50-sheet stapler)		097S04952		
4-Bin Mailbox (100 sheets per bin)		097S04953		
Productivity Kit with 320 GB HDD		497K18360		
Wireless Network Adapter (Wi-Fi Kit)		497K16750		

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.



Declared print speed in accordance with ISO/IEC 24734.
 Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.
 Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

Prover states definited pet ENEART FIRST Flogramme requirements for analysing Equipments.

Requires analogue phone line.

Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks

Average standard pages. Declared yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/latest/SUPGL-01.pdf