

# Xerox® VersaLink® C8000 Colour Printer



The VersaLink® C8000 Colour Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.co.uk.

SYSTEM SPECIFICATIONS	VERSALINK® C8000DT	
One-Sided Speed <sup>1</sup> A4 A4 SEF 216 x 356 mm A3/297 x 420 mm/ SRA3/320 x 450 mm	Up to 45 ppm (pages per minute) long edge feed (LEF) Up to 32 ppm Up to 26 ppm Up to 22 ppm	
Two-Sided Speed <sup>1</sup> A4 A4 SEF 216 x 356 mm A3/297 x 420 mm/ SRA3/320 x 450 mm	Up to 45 ppm LEF Up to 32 ppm Up to 17 ppm Up to 15 ppm	
Monthly Duty Cycle <sup>2</sup>	Up to 205,000 pages/month	
Recommended Average Monthly Print Volume <sup>3</sup>	Up to 20,000 pages per month	
Hard Drive	320 GB HDD (Optional)	
Processor	1.6 GHz Dual-Core	
Memory	4 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan	

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS	ELECTRICAL REQUIREMENTS			
North America		Voltage: 110-127 V +/-10 % Frequency: 50/60 Hz +/-3 %, 12 A		
Europe and Other Geographies	Voltage: 220-240 V Frequency: 50/60 Hz			
POWER CONSUMPTION				
Printing <sup>4</sup>	For 110 V: 2.30 kWh For 220 V: 2.32 kWh			
Standby Mode <sup>4</sup>	110 V: 75.3 Watts or 220 V: 73.8 Watts or			
Sleep Mode <sup>4</sup>	0.67 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	Below 48° C, and in a	compliance with MN2-81	0.13	
Required Temperature Range (Operating)	10° to 28° C Must be 28° C or bel	ow if humidity is at 85%		
Required Relative Humidity	15% to 85% Must b	oe 62.5% or below at 32	°C	
Sound Power Levels	Printing: 6.63 B(A) or less Standby: 3.24 B(A) or less Full System (including finisher) Printing: 7.56 B(A) Standby: 3.36 B(A)			
Sound Pressure Levels	Printing: 56.8 dB or less Standby: 15.4 dB or less  Full System (including finisher) Printing: 57.1 dB Standby: 15.2 dB			
Boot Time (from Off to UI Ready)	Less than 60 seconds			
Warm-up Time (from Sleep to UI Ready)	Less than 10 seconds (without HDD) Less than 16 seconds (with HDD)			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C8000/DT	620 mm	723 mm	809.3 mm	80.8 kg
Two Tray Module	668.5 mm	723 mm	261.2 mm	27.2 kg
Tandem Tray Module	668.5 mm	723 mm	261.2 mm	33.8 kg
High Capacity Feeder	389 mm	602.9 mm	380.01 mm	29.0 kg
Office Finisher LX	559.8 m m	552 mm	1012 mm	28.0 kg
Office Finisher with Booklet Maker attached	1513 mm 723 mm 1076 mm 151.6 kg			
BR Booklet Maker Finisher	769.2 mm 723 mm 1055.1 mm 60.9 Kg			

DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C8000/DT	833 mm	717 mm	852 mm	95 kg
High Capacity Feeder	526 mm	756 mm	491 mm	33.7 kg
Two Tray Module	830 mm	850 mm	400 mm	33 kg
Tandem Tray Module	830 mm	850 mm	400 mm	39 kg
Office Finishers	690 mm	1021 mm	654 mm	37 kg
Booklet Maker Finisher	507 mm	761 mm	437 mm	14 kg
BR Booklet Maker Finisher	764 mm	774 mm	1203 mm	77 kg
Horizontal Transport for BR Booklet Maker Finisher	533 mm	589 mm	319 mm	6.5 kg

## **CERTIFICATIONS**

To view the latest list of certifications, go to <a href="https://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a>.

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.		
PRINT		
First-Print-Out Time	As fast as 11 seconds colour	
	As fast as 11 seconds black and white	
Print Resolution	Up to 1200 x 2400 dpi	
Page Description Languages	Adobe® PostScript® 3™ PCL® 5c, 6 PDF XPS TIFF JPEG HP-GL	
Colour Management	Embedded spot colour table, Xerox Colour Corrections	
Maximum Print Area	4 mm from lead edge of paper, 2 mm from side and trail edges of paper	
Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Colour Adjustments (lightness, contrast, saturation, colour balance) Colour Correction Draft Mode Finishing (requires finishing) Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages)	

	Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing (as default) Watermark (predefined and custom) Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® UNIX® Note: For information about supported versions for the above operating systems, please visit our Drive & Downloads page and specify your device at www.support.xerox.com/en-gb.	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management.	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharo® and others.	
MOBILE SOLUTIONS AND MOBI	LE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria certification ensures you can print wirelessly from your Mopria-supported (Android™) smartphone, tablet and other mobile devices instantly and easily.	
Xerox® @printbyXerox App	@printbyXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or multifunction printer using a single email address with no IT intervention. No training is needed. End users simply send attachments to the email address and release them at the panel on the multifunction printer.	
Xerox® Print Services Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.	

Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Solutions be mobility solution. Control and workflows, convenience and se flexible licence options to suit o  Xerox® Workplace Suite: Or

poost productivity and reduce costs with a modular print management and manage your printer fleet while enabling mobile productivity with simplified ecurity – for any brand printer, anywhere. Xerox® Workplace Solutions offer any size business with the ability to scale as you grow.

- n-site, your server
- Xerox® Workplace Cloud: Simple set-up, cloud administration

To learn more about the Xerox® Workplace Suite and Xerox® Workplace Cloud, visit www.xerox.co.uk/en-gb/office/software-solutions/xerox-workplace-cloud.

#### **SOFTWARE SOLUTIONS**

Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery App)

Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the device.

#### **SECURITY**

Security Features **Access Controls** AES 256-bit encryption Audit log Certificate path validation

Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external program falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration

Domain Filtering FIPS 140-2 Firmware Verification

Immediate Disk Overwrite\* IP Address Filtering **IPsec** 

Network Authentication

Port Filtering

Pre-installed Self-Signed Certificates

Role Based Permissions

Secure Print

Security Certificate Management Smart Card Enablement (CAC/PIV/.NET)

SNMPv3

Status Protocol (OCSP)

TLS/SSL

Trusted Platform Module (TPM)

\*Requires HDD/Productivity Kit

### **ACCOUNTING**

## XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)

Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General accounts  Network Accounting (Job-Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.

ACCOUNTING OPTION	IS – NETWORK ACCOUNTING (ALL	OWS CENTRAL SERVER TO MANAGE A	LL ACCOUNTING)	
	<ul> <li>Comprehensive mana</li> <li>Numerous solutions ar</li> <li>Security enhancement</li> <li>Device requests account</li> </ul>	counting with up-to-the-minute data on hogement and enterprise-scale tracking and e available through Xerox Alliance Partnets include simultaneous support for HTTP/nt authentication from third-party server, a Login at control panel and pass to third-party	reporting of device print usage rs. For details visit www.xerox.co.uk HTTPS protocols enabling larger databases of users	
PAPER HANDLING				
BYPASS TRAY				
Capacity <sup>5</sup>	100 sheets			
Sizes	Custom sizes: 88.9 x 98.4 Banners: 88.9 x 98.4 mm	4 mm to 320 x 482.6 mm n to 320 x 1320.8 mm		
Weights	Simplex and Duplex: 64	to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Envelopes Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Card Stock	Lightweight Glossy Cardstock Pre-Printed Postcards Recycled	
TRAY 1 AND 2				
Capacity <sup>5</sup>	520 sheets each			
Sizes	Tray 1: 100 x 148 mm to Tray 2: 100 x 148 mm to			
Weights	Simplex and Duplex: 64	to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Card Stock Lightweight Glossy Cardstock Pre-Printed Recycled	
TWO TRAY MODULE				
Capacity <sup>5</sup>	1,040 sheets			
Sizes	Custom sizes: 100 x 148	Custom sizes: 100 x 148 mm to 320 x 457.2 mm		
Weights	Simplex and Duplex: 64	Simplex and Duplex: 64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Card Stock Lightweight Glossy Cardstock Pre-Printed Recycled	

TANDEM TRAY MODULE			
Capacity <sup>5</sup>	2,000 sheets		
Sizes	A4, B5		
Weights	Simplex and Duplex: 64 to 300 gsm		
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock	Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead	Lightweight Card Stock Lightweight Glossy Cardstock Pre-Printed Recycled
HIGH CAPACITY FEEDER	•		
Capacity <sup>5</sup>	2,000 sheets		
Sizes	A4, B5		
Weights	64 to 216 gsm		
Types	Bond Plain Paper Cardstock Custom	Glossy Cardstock Hole Punched Letterhead Lightweight Card Stock	Lightweight Glossy Cardstock Recycled
ENVELOPE TRAY – REPLACES TRA	AY 1 (OPTIONAL)		
Capacity <sup>5</sup>	Up to 50 envelopes		
Sizes	No. 10 commercial, Mor Custom sizes: 90 x 98 m		
TOTAL CAPACITY			
VersaLink® C8000/DT Capacity <sup>5</sup>	1,140 sheets		
Maximum Capacity⁵	5,140 sheets		
FINISHING			
OUTPUT TRAYS	_		
<b>Dual Offset Catch Tray</b> (Standard when finishers are not attached)	500 sheets (without centre tray) 2x 250 sheets (with centre tray when offset is off) 2x 125 sheets (with centre tray when offset is on)		
OFFICE FINISHERS (OPTIONAL)			
Capacity <sup>5</sup>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (A4 to A3)		
Sizes Office Finisher LX Office Finisher	210 x 182 mm to 297 x 432 mm 148.0 to 297.0 mm x 148.0 to 432.0 mm		
Weights Office Finisher LX Office Finisher	60 to 220 gsm 60 to 256 gsm		
Multi-position Stapling	50 sheets of 90 gsm		
Hole Punch (Optional) North America: Europe and Other Geographies:	Office Finisher LX: up to 200 gsm/Office Finisher: up to 220 gsm 2/3 hole punch 2/4 hole punch		
BOOKLET MAKER FOR OFFICE FI	NISHERS (SCORE/CREAS	E, SADDLE-STITCH STAPLE) (OPTIONA	L)
Capacity <sub>5</sub>	40 booklets (2 to 15 she	ets per booklet – 80 gsm or less)	
Sizes	Letter – A4 SEF Legal – B4 SEF Ledger – A3 SEF		

Saddle-stitch Stapling	2 to 15 sheets/8-60 page booklet 60 to 90 gsm	
Score/Crease	1 to 15 sheets/unstapled/60 to 105 gsm only	
OPTIONAL BR BOOKLET MAKER FINISHER (REQUIRES HORIZONTAL TRANSPORT KIT)		
Capacity <sup>5</sup>	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4/A3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3	
Sizes	A6 to A3 for stacking B5 to A3 for stapling	
Weights	60 to 300 gsm (coated and uncoated)	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported	
<b>Hole Punch</b> North Americα Europe	2/3 hole punch 2/4 hole punch 4 hole "Swedish" punch (optional)	
Booklet maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	
DEVICE MANAGEMENT		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
REMOTE CONTROL PANEL		
	<ul> <li>Enables faster, more convenient technical support and user training</li> <li>IT administrators and other authorised users can control the device remotely from a web page on any device</li> <li>Remote user experience is identical to performing tasks directly at the device</li> </ul>	
XEROX® CENTREWARE® WEB		
	<ul> <li>A web-based server application for network administrators that permits web-browser-based device management from any workstation, whether running Windows, UNIX or any other operating system</li> <li>Works with any SNMP-managed printer from any manufacturer</li> <li>Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>	
XEROX® EMBEDDED WEB SERVE	R – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul> <li>Tray status/Contents</li> <li>Consumables Status</li> <li>Billing/Usage</li> <li>Quick Links</li> <li>Online Support</li> </ul>	
Print Queue Viewing	Job print queue management – view and delete	
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	

Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™		
REMOTE SERVICES			
Xerox® Automated Meter Reads (AMR)	Automates the process of collecting and submitting meter re- usage. Eliminates the need for time-consuming end-user invo submitted to Xerox on time.	ads for tracking and billing of Xerox® device Ivement and ensures that meter reads are	
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices base manually manage supplies inventory.	d on actual usage, eliminating the need to	
WHAT'S IN THE BOX			
	<ul> <li>VersaLink® C8000 Colour Printer</li> <li>Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow: 8,000 print capacity<sup>6</sup>, Black: 12,000 print capacity)<sup>6</sup></li> <li>Drum Cartridge – One of each (Cyan, Magenta, Yellow, &amp; Black: 190,000 print capacity)<sup>7</sup></li> <li>Quick Use Guide</li> <li>Install Guide</li> <li>Software and Documentation CD (with Drivers, Warranty Statement and Safety Regulatory Recycle Disposal Guide)</li> <li>Power Cord</li> </ul>		
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER	
SUPPLIES			
Standard Capacity Toner Cartridges	Cyan: 7,600 standard pages <sup>6</sup> Magenta: 7,600 standard pages <sup>6</sup> Yellow: 7,600 standard pages <sup>6</sup> Black: 12,600 standard pages <sup>6</sup>	106R04038 106R04039 106R04040 106R04041	
High Capacity Toner Cartridges	Cyan: 16,500 standard pages <sup>6</sup> Magenta: 16,500 standard pages <sup>6</sup> Yellow: 16,500 standard pages <sup>6</sup> Black: 20,900 standard pages <sup>6</sup>	106R04050 106R04051 106R04052 106R04053	
Drum Cartridge	Cyan: 190,000 standard pages <sup>7</sup> Magenta: 190,000 standard pages <sup>7</sup> Yellow: 190,000 standard pages <sup>7</sup> Black: 190,000 standard pages <sup>7</sup>	101R00602	
Waste Cartridge	47,000 standard pages <sup>7</sup>	108R01504	
IBT Cleaner	160,000 standard pages <sup>7</sup>	104R00256	
Transfer Roller	200,000 standard pages <sup>7</sup>	116R00015	
Office Finisher Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897	
Staple Refills for Office Finisher (3 refills per container)	15,000 staples (5,000 each refill)	008R12941	
Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964	
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177	

## Xerox® VersaLink® C8000 Colour Printer

ACCESSORIES/OPTIONS	
Two Tray Module	097S04969
Tandem Tray Module	097S04970
High Capacity Feeder	097S04845
Envelope Tray (Replaces Tray 1)	497K17880
Office Finisher LX (Includes Gap Filler)	097S04848 497K17370
Office Finisher	097S05019
2/3 Hole Punch for Office Finisher LX (available Western Hemisphere)	497K03860
2/3 Hole Punch for office finisher (available Western Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher LX (available Western Hemisphere)	497K03870
2/4 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20610
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
BR Booklet Maker Finisher with 2/3 Hole Punch (comes with Horizontal Transport)	497K21000
BR Booklet Maker Finisher with 2/4 Hole Punch	097S04982
Swedish 4 Hole Punch for BR Finisher	497K14370
320 GB HDD	097S04971
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120 (Western Hemisphere) 497K18140 (Eastern Hemisphere)

<sup>&</sup>lt;sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling programme. For more information, visit www.xerox.co.uk/recycling.

For more information, visit us at www.xerox.co.uk/office.

Configurations vary by geography.



<sup>Declared print speed in accordance with ISO/IEC 24734.

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.

Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/latest/SUPGL-01.pdf.</sup>